

Domae - comb busbar - 1L - 18 mm pitch - 57 modules - 63A





Main

Range	Domae
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	57

Complementary

•	
Number of ways	57 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	18 mm
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-1
Mounting location	Top on tunnel type terminals
9 mm pitches	114
Width	1000 mm
Colour	Light grey (RAL 7035)
Range compatibility	Easy9 MCB Easy9 RCBO Easy9 RCCB Easy9 switch Domae

Environment

Standards	IEC 60664 EN/IEC 60439-1
Fire resistance	850 °C (30 s) conforming to IEC 60695-2-1

D-U-Alexanderson	
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	175.0 g
Package 1 Height	1.5 cm
Package 1 Width	2.5 cm
Package 1 Length	101.7 cm
Unit Type of Package 2	P12
Number of Units in Package 2	2700
Package 2 Weight	485.904 kg
Package 2 Height	92.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	50
Package 3 Weight	8.776 kg
Package 3 Height	104.0 cm
Package 3 Width	10.0 cm
Package 3 Length	11.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Contraction warranty		
Warranty	18 months	